

Maps2mapc



This page is obsolete and will be reworked soon

How create a sqlitedb file with Maps2mapc

Basic information

- Locus currently support wide range of map formats (more [here](#)). But most common formats are not yet covered. If you want convert your maps to some format usable by Locus, you may look on program [MAPC2MAPC](#).
- Firstly, suggest to test working demo version if this fits your needs. [Here](#) is description from author of MAPC2MAPC, how to...
- In case you'll be satisfied, I suggest to buy full version by **Buy** button on bottom of manual page. Thanks to this, you'll get 10% discount of this product
- **MAPC2MAPC**: <http://www.the-thorns.org.uk/mapping/>

Additional knowledge base information

- [Convert IMG maps to a sqlitedb Locus map](#)
- [Convert pictures to a sqlitedb Locus map](#)

Additional forum information

<http://forum.locusmap.eu/viewtopic.php?f=10&t=413&p=1876&hilit=MAPC2MAPC#p1876>
<http://forum.locusmap.eu/viewtopic.php?f=21&t=4&p=4874&hilit=MAPC2MAPC#p4874>
<http://forum.locusmap.eu/viewtopic.php?f=44&t=899&p=5043&hilit=MAPC2MAPC#p5043>
<http://forum.locusmap.eu/viewtopic.php?f=21&t=3&p=6142&hilit=MAPC2MAPC#p6142>
<http://forum.locusmap.eu/viewtopic.php?f=21&t=3&p=12802&hilit=MAPC2MAPC#p12802>

Various

How to convert Netherlands TOP25raster

The Netherlands kartographic service PDOK offers topographic map Topo25raster for free. These map are provided in geoTiff format in local coordinate system. Locus is not able to handle geoTiff format for this reason is needed to convert these data manually.

This tutorial is prepared for Windows system but especially GDAL utilities work little bit better on Linux systems.

Download data

- Whole Netherland is devided into section – download section which is suitable for you
- Download page:
<https://www.pdok.nl/nl/producten/pdok-downloads/basis-registratie-topografie/topraster/top25raster-d...>

Use GDAL for transformation

Install GDAL

- For purpose of this tutorial download gdal
<http://www.gisinternals.com/sdk/PackageList.aspx?file=release-1600-gdal-1-10-0-mapserver-6-2-1.zip>
- Download gdal-110-1600-core.msi installer

Transform downloaded geotif

- Open command line (CMD) and go to the GDAL installation folder (in our case cd C:\Program Files (x86)\GDAL)
- Transform downloaded geoTiff into WGS84 system

```
set GDAL_DATA=.\\gdal-data
gdalwarp -t_srs EPSG:4326 44a-top25raster-2010.tif 44a-top25raster-2010-4326.tif
```

Generate map using Mapc2Mapc into Locus format

- Download and install SW Mapc2Mapc <http://www.the-thorns.org.uk/mapping/down.htm>
- Start Mapc2mapc and set the location of gdal_translate
 - Edit > Locate > GDAL_translate (choose path to the installation folder of gdal)
- Open transformed geoTiff
 - File > Load Calibrated map
- Export file for Locus
 - File > Write map for Mobile devices
 - Choose Locus/RMAPS sqlitedb
 - Set zoom levels
 - optional: check Make tile margins transparent

- Press OK and confirm all zoom levels which will be generated

Import map into Locus

- Copy generated sqlitedb map into your device folder Locus/maps
- Start Locus

Red crosses

- The demo version of mapc2mapc will add random red crosses over the map. This is limitation of free/demo version

[44a-top25raster-2010-4326.zip](#)

How To Convert Shp File For Locus

- Locus type: `<html>FreePro</html>`, **2.3.0+**
- Last updated manual: **2.3.0**


Basic information

Locus basically does not support SHP file at this moment. On the other hand there are some possibilities how to convert SHP to the different format that is possible to import into Locus.


Convert SHP file to KML

Probably the easiest way is convert SHP file into KMZ file which is fully supported by Locus. Unfortunately there is a limitation in size of KML file. The **limit** for Locus is about **5000 - 10000 points** depends on your device.


- Download free tool Shp2kml <http://www.zonums.com/files/Shp2kml.zip>
- Unzip and run shp2kml.exe
- On the first screen select file for convert



- Define color for lines/polygons



- Skip balloon definition screen
- On the last screen define name of layers and description



- Create KML file
- Copy created KML file into Locus/mapItems
- Run Locus and go to the Data manager > tab Items



Convert SHP to Mapsforge format

In this example we expect that shp file for converting is very simple. Unfortunately converting is little bit tricky and requires a specific approach for particular SHP files. So it is not possible to say that this example could be used for every SHP file.

For this example we use free shp data (Czech Republic boundaries) download-able at http://gadm.org/data/shp/CZE_adm.zip.

SHP file to OSM format

There are lots of possibilities how to do it - see <http://wiki.openstreetmap.org/wiki/Shapefiles>. In this example we use Merkaartor SW.

- Download Merkaartor <http://merkaartor.be/wiki/merkaartor/Download>
- Run it and open SHP file for converting
- Export OSM: File > Export > OSM (XML)
- Note: Merkaartor place <bound> tag in the end of osm.xml file. You need move it and place whole tag before first geometry element

[cze_adm.osm](#)

```
<?xml version="1.0"?>
<osm generator="Merkaartor 0.17" version="0.6">
  <bound box="48.540841,12.085860,51.054381,18.862533"
  origin="http://www.openstreetmap.org/api/0.6"/>
  <node version="0" lon="14.4138160" lat="49.2553340"
  timestamp="2013-04-28T10:55:33Z" user="" id="-1" actor="0"/>
  . . .
  . . .
```

...

Mapsforge map writer plugin

Osmosis


- Download and install osmosis 0.40.1
<http://bretth.dev.openstreetmap.org/osmosis-build/osmosis-0.41.zip>
- Note: there are newest version of osmosis but Map writer plugin does not work properly with them
- More details about osmosis <http://wiki.openstreetmap.org/wiki/Osmosis/Installation>

Map writer plugin

- Download Mapwriter plugin [mapsforge-map-writer-0.5.0-jar](#)
- Copy downloaded plugin into osmosis folder osmosis/plugins .
- More about installing Map writer plugin:
<https://github.com/mapsforge/mapsforge/blob/master/docs/Getting-Started-Map-Writer.md#plugin-installation>

Define custom tags for generation of map file

- Map writer plugin uses a XML file(tag-mapping.xml) which contains pairs of known tags for generation. This xml define which OSM element will be included in the map file.
- Use Merkaartor or arbitrary GIS/DBF viewer and decide which SHP attributes you want to export to the map file.
- For this example we create tag-mapping-shp.xml file based on tag _ENGTYPE_2_



Key	Value
_CC_2_	
_ENGTYPE_2_	District
_HASC_2_	
_ID_0_	59
_ID_1_	749
_ID_2_	11503

[tag-mapping-shp.xml](#)

```
<?xml version="1.0" encoding="UTF-8"?>
<tag-mapping xmlns="http://mapsforge.org/tag-mapping"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://mapsforge.org/tag-mapping
```

```

../resources/tag-mapping.xsd" default-zoom-appear="16"
profile-name="default-profile">

  <!-- CZE_ADM_2 -->
  <ways>
    <osm-tag key="_ENGTYPE_2_" value="District" zoom-appear="4"
force-polygon-line="true" />
    <osm-tag key="_ENGTYPE_2_" value="Statutory city" zoom-
appear="4" force-polygon-line="true"/>
  </ways>
</tag-mapping>

```

Generate map file

- Run generation

```

bin\osmosis.bat --read-xml cze_adm.osm --mapfile-writer file=cze_adm.osm.map
type=ram tag-conf-file=tag-mapping-shp.xml bbox-enlargement=0

```

- More information about generation and Mapwriter plugin
<https://github.com/mapsforge/mapsforge/blob/master/docs/Getting-Started-Map-Writer.md>

Create vector theme for rendering

- We've generated vector map and in next step we need to define appearance of geometry. Appearance is defined via theme XML.
- You can edit any free theme for Locus or create new one which will be created especially for your SHP file.
- Create theme xml (in our case cze_adm_theme.xml)

cze_adm_theme.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<rendertheme xmlns="http://mapsforge.org/renderTheme"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://mapsforge.org/renderTheme
../renderTheme.xsd"
locus-extended="1" fill-sea-areas="0" version="1" map-
background="#00FFFFFF">


  <!-- Render Boundaries -->
  <rule e="way" k="*" v="*">
    <rule e="way" k="_ENGTYPE_2_" v="District" >
      <line stroke="#FF3E96" stroke-width="4" />
    </rule>
    <rule e="way" k="_ENGTYPE_2_" v="Statutory city">
      <line stroke="#B56904" stroke-width="4" />
    </rule>
  </rule>

```

```
</rule>  
</rendertheme>
```

Copy map and theme to the device

- Copy vector map file `cze_adm.osm.map` into folder `Locus/mapsVector`
- Copy theme xml into folder `Locus/mapsVector/_themes`



From:
<http://docs.locusmap.eu/> - Locus Map Classic - knowledge base

Permanent link:
http://docs.locusmap.eu/doku.php?id=manual:advanced:map_tools:conversion&rev=1432218477

Last update: 2015/05/21 16:27

