Conversion of Maps

How to create a sqlitedb file with Mapc2mapc

Mapc2mapc is not a product of Asamm Software so we do not take any responsibility for changes in its usage. This article is for general information only.

Basic information

- Locus Map currently supports a wide range of map formats (see more here >>). But many other formats are not yet covered. If you want to convert your maps to some format usable by Locus Map, have a look at MAPC2MAPC software.
- Firstly we recommend to test the demo version if this fits your needs. Here are instructions of the MAPC2MAPC author.
- In case you are satisfied we suggest to buy the full version

Locus Map Classic user gets 10% discount of this product. Read more >>

• MAPC2MAPC: http://www.the-thorns.org.uk/mapping/

Additional manual chapters

- Converting IMG maps to a Locus supported sqlitedb map
- Converting pictures to a Locus supported sqlitedb map

Additional forum information

http://forum.locusmap.eu/viewtopic.php?f=10&t=413&p=1876&hilit=MAPC2MAPC#p1876 http://forum.locusmap.eu/viewtopic.php?f=21&t=4&p=4874&hilit=MAPC2MAPC#p4874 http://forum.locusmap.eu/viewtopic.php?f=44&t=899&p=5043&hilit=MAPC2MAPC#p5043 http://forum.locusmap.eu/viewtopic.php?f=21&t=3&p=6142&hilit=MAPC2MAPC#p6142 http://forum.locusmap.eu/viewtopic.php?f=21&t=3&p=12802&hilit=MAPC2MAPC#p12802

Various

How to convert Netherlands Top25raster

The Netherlands kartographic service PDOK offers topographic map Top25raster for free. These maps are provided in geotiff format in local coordinate system. Locus Map is not able to handle geotiff format, therefore it is necessary to convert these data manually.



This tutorial is prepared for Windows system but especially GDAL utilities work a little bit better on Linux systems.

Download data

- Whole Netherland is divided into sections download a section which is suitable for you
- Download page:

https://www.pdok.nl/nl/producten/pdok-downloads/basis-registratie-topografie/topraster/toprast er-actueel/top25raster and other scales

Use GDAL for transformation

Install GDAL

- For purpose of this tutorial download gdal http://www.gisinternals.com/sdk/PackageList.aspx?file=release-1600-gdal-1-10-0-mapserver-6-2 -1.zip
- Download gdal-110-1600-core.msi installer

Transform downloaded geotiff

- Open command line (CMD) and go to the GDAL installation folder (in our case C:\Program Files (x86)\GDAL)
- Transform downloaded geotiff into WGS84 system

set GDAL_DATA=.\gdal-data
gdalwarp -t_srs EPSG:4326 44a-top25raster-2010.tif 44atop25raster-2010-4326.tif

Use Mapc2Mapc to generate map in a Locus-supported format

- Download and install Mapc2Mapc http://www.the-thorns.org.uk/mapping/down.html
- Start Mapc2mapc and set the location of gdal_translate
 - Edit > Locate > GDAL_translate (choose path to the installation folder of gdal)
- Open transformed geotiff
 - File > Load Calibrated map

- Export file for Locus
 - File > Write map for Mobile devices
 - Choose Locus/RMAPS sqlitedb
 - Set zoom levels
 - optional: check Make tile margins transparent
 - $\circ\,$ Press OK and confirm all zoom levels that will be generated

Import map into Locus Map

- Copy generated sqlitedb map into your device folder Locus/maps
- Start Locus Map

Red crosses

• The demo version of Mapc2mapc will add random red crosses over the map. This is limitation of free/demo version

44a-top25raster-2010-4326.zip

How To Convert Shp File For Locus

Basic information

Locus Map basically does not support SHP files at this moment. On the other hand there are some possibilities how to convert SHP to a different format that can be imported into Locus Map.

Convert SHP file to KML

Probably the easiest way of converting SHP file which is fully supported by Locus. Unfortunately there is a limitation in size of KML file. The **limit** for Locus Map is about **5000 – 10000 points** depending on your device.

- Download free tool Shp2kml http://www.zonums.com/files/Shp2kml.zip
- Unzip and run shp2kml.exe
- Select the file for conversion on the first screen

Last update:	manual:advanced:map_tools:conversion https://docs.locusmap.eu/doku.php?id=manual:advanced:map_tools:conversion
2022/04/07 11:54	

128	Shp2kmi	2.1b	-		
Shapefile to Google Earth			🔳 🚳	M 🕹 (9
Input File (*.shp) D.lasamm/maps\shp\lesn	_cesty_SK	LC_nove-S	HPVc2-N	shp 🔒	3
Shape Type: Polyline Coordinate System Datum					
WGS 1984 Global Definiti Ellipsoid: WGS 84	on			•	9
Units @ Geographic: Lati	Lon				
C Projected UTM (UTM Zone Zone 1	neters) 12 • s	Northern	Hemisphe see fre U	TM_Grid	
www.accume.com		Ne	e>> [Oane	כ

• Define color of lines/polygons

12		Shp2kml 2.1b	- O X
Shapofile	to Google Ea	💷 🖾 🔕 🔛 😣 😣	
	Singl	e Symbol	
	_		
	Click	to Change	
WW. 3	count.com	<< Back	Next >> Close

- Skip balloon definition screen
- Define name of layers and description on the last screen

12	Shp2kml 2.1b	×
Shapefile to Google Earth		💷 💷 🙆 👪 🍛 🐵
Layer Title		
Forest ways		
Description		
Slovakia		
Altitude Mode Clamped	to Ground 💌	Tessellate
T 3D Options		
C Use Elevation Value		
C Constant Value		
C Entrance	-	
4+ THES VALUE		Pactor W
Create KML file	Cn	eate and Open
www.sonung.com	<< Back	Cone

- Create KML file
- Copy created KML file into Locus/mapItems
- Run Locus Map and go to the Data manager > tab Items



Convert SHP to Mapsforge format

In this example we expect that shp file for converting is very simple. Unfortunately converting is little bit tricky and requires a specific approach for particular SHP files. So it is not possible to say that this example could be used for every SHP file.

For this example we use free shp data (Czech Republic boundaries) download-able at http://gadm.org/data/shp/CZE_adm.zip.

SHP file to OSM format

There are lots of possibilities how to do it - see http://wiki.openstreetmap.org/wiki/Shapefiles. In this example we use Merkaartor SW.

- Download Merkaartor http://merkaartor.be/wiki/merkaartor/Download
- Run it and open SHP file for converting
- Export OSM: File > Export > OSM (XML)
- Note: Merkaartor place <bound> tag in the end of osm.xml file. You need to move it and place whole tag before first geometry element

cze_adm.osm

```
<?xml version="1.0"?>
<osm generator="Merkaartor 0.17" version="0.6">
        <bound box="48.540841,12.085860,51.054381,18.862533"
origin="http://www.openstreetmap.org/api/0.6"/>
        <node version="0" lon="14.4138160" lat="49.2553340"
timestamp="2013-04-28T10:55:33Z" user="" id="-1" actor="0"/>
        ...
```

• • •

Mapsforge map writer plugin

Osmosis

- Download and install osmosis 0.40.1 http://bretth.dev.openstreetmap.org/osmosis-build/osmosis-0.41.zip
- Note: there are newer versions of Osmosis but the Map writer plugin does not work properly with them
- More details about Osmosis http://wiki.openstreetmap.org/wiki/Osmosis/Installation

Map writer plugin

- Download Mapwriter plugin mapsforge-map-writer-0.5.0-jar
- Copy downloaded plugin into Osmosis folder osmosis/plugins .
- More about installing Map writer plugin: https://github.com/mapsforge/mapsforge/blob/master/docs/Getting-Started-Map-Writer.md#plu gin-installation

Define custom tags for generation of map file

- Map writer plugin uses a XML file (tag-mapping.xml) that contains pairs of known tags for generation. This xml defines which OSM element will be included in the map file.
- Use Merkaartor or arbitrary GIS/DBF viewer and decide which SHP attributes you want to export to the map file.
- For this example we create tag-mapping-shp.xml file based on tag _ENGTYPE_2_

ags		s 🗙
Key	Valu	e 🔺
_CC_2_		
_ENGTYPE_2_	District	
HASC_2_		_
_ID_0_	59	
_ID_1_	749	
_ID_2_	11503	

tag-mapping-shp.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<tag-mapping xmlns="http://mapsforge.org/tag-mapping"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://mapsforge.org/tag-mapping
../resources/tag-mapping.xsd" default-zoom-appear="16"
```

Generate map file

• Run generation

```
bin\osmosis.bat --read-xml cze_adm.osm --mapfile-writer file=cze_adm.osm.map
type=ram tag-conf-file=tag-mapping-shp.xml bbox-enlargement=0
```

 More information about generation and Mapwriter plugin https://github.com/mapsforge/mapsforge/blob/master/docs/Getting-Started-Map-Writer.md

Create vector theme for rendering

- We've generated vector map and in next step we need to define appearance of geometry. Appearance is defined via theme XML.
- You can edit any free theme for Locus or create new one which will be created especially for your SHP file.
- Create theme xml (in our case cze_adm_theme.xml)

cze_adm_theme.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<rendertheme <pre>xmlns="http://mapsforge.org/renderTheme"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://mapsforge.org/renderTheme
../renderTheme.xsd"
  locus-extended="1" fill-sea-areas="0" version="1" map-
background="#00FFFFFF">
    <!-- Render Boundaries -->
    <rule e="way" k="*" v="*">
        <rule e="way" k=" ENGTYPE 2 " v="District" >
                        <line stroke="#FF3E96" stroke-width="4" />
        </rule>
        <rule e="way" k=" ENGTYPE 2 " v="Statutory city">
            <line stroke="#B56904" stroke-width="4" />
        </rule>
    </rule>
```

</rendertheme>

Copy map and theme to the device

- Copy vector map file cze_adm.osm.map into folder Locus/mapsVector
- Copy theme xml into folder Locus/mapsVector/_themes



From: https://docs.locusmap.eu/ - Locus Map Classic - knowledge base

Permanent link: https://docs.locusmap.eu/doku.php?id=manual:advanced:map_tools:conversior

Last update: 2022/04/07 11:54

